## FOR VERNON COUNTY, WISCONSIN


Note: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, AE-7.08, U.S. Public Land Survey Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i). Use additional a necessary. additional sheets , Chapter sheets if

(a) Sections

Township(s) 14 North, Range(s) 07 West.

Vernon County Coordinates: z 199855.374

625071.057



testimonial, occupational, plats records, other monuments) used as a basis for accepting. If not accepted or nothing was found, state evidence used as basis for established through lost corner proportionate methods, indicate all monuments, distances nothing was found, state evidence used as basis for establishing location and what was set. (b)(f)(h) Description of monument found at this corner and if it was accepted, and directions used state all evidence (material,

1846-1847 Alfred L. corner of Section 11. Brown established original corner location 39.92 1/2 chains East of the Southwest

November 17, 1998 - I found a 2" Iron Pipe with a pinched top which fit occupation to the north and prorated distances across the south line of Section 11. I accepted it as the corner, replaced it with a Vernon County, and set witnesses as shown.

NORTH established corner, show the distances between the two corners and also Chipmunk N 89°W Ridge Drive Field indicate ties to disputed corner

(c)(d)(e) Plan view of corner with ties to at lest four (4) witness monuments. If in disagreement with previously

Not To Scale 数 = Placed Vernon County Monument Wooded 18.64 24"\ Elms Wood Witness 

Post

Placed 60d spike

(I) Certify that the corner location on this record was determined by me or under my direction and control and that this U.S. Public Land survey Monument Record is correct and complete to the best of my knowledge and belief

Signature Carl M. Sandsnes

Filed for record in Vernon County Surveyor's Office on

December 31, 1998.
Date

INDEX NO.

